

DIN RAIL SOCKET

For mounting on 35 mm DIN rail. Wire connections on terminals. It provides a power supply for electrical tools or instruments during installation, operation and maintenance. Available in five different national standards and in two basic versions: without and with limiting fuse 6.3A.



Features	Unit	ALFASOCKET01	ALFASOCKET02	ALFASOCKET03	ALFASOCKET04	ALFASOCKET05
Standard	-	Germany	Italy	France	Euro-American	Spain
Voltage	V	250	250	250	125	250
Max current	A	16	16	16	16	16
Electrical connections	-	3-pole terminal for 2.5 mm ² wire				
Casing	-	ABS, UL94 V0 self-extinguishing, light grey RAL 7035				
Protection degree	-	IP20				
Protection class	-	Class I				
Operating temperature	-	-25/+60 (-13/+140)				
Storage temperature	°C (°F)	-45/+60 (-49/+140)				
Mounting	-	Clip for mounting on DIN rail 35 mm EN50022				
Conformity	-	CE				
Dimensions HxWxD	mm	92x57x51				
Weight	g	105				

Versions

with fuse 6.3 A	ALFASOCKET01F	ALFASOCKET02F	ALFASOCKET03F	ALFASOCKET04F	ALFASOCKET05F
-----------------	---------------	---------------	---------------	---------------	---------------

Accessories

GUIDADINPL	GUIDADINPL	GUIDADINPL	GUIDADINPL	GUIDADINPL	GUIDADINPL
------------	------------	------------	------------	------------	------------

