



Model	Dimensions	Cut-Out	Rated Voltage	Rated Power	Max Airflow	Airflow with Exhaust Filter	Approvals
	mm	mm	V	W	m³/h	m³/h	
FF15PD							
FF15PD24UN	250x250x112	223x223	24 V d.c.	7,6	140	105	UR; cULus; cCSAus
FF15PD24UNR	250x250x112	223x223	24 V d.c.	7,6	150	124	UR; cULus; cCSAus
FF15PD48UN	250x250x112	223x223	48 V d.c.	8,6	140	105	UR; cULus; cCSAus
FF15PD48UNR	250x250x112	223x223	48 V d.c.	8,6	150	124	UR; cULus; cCSAus
FF20A							
FF20A115UE	325x325x161	291x291	115 V a.c.	100/129	445/490	320/350	-
FF20A115UE1	325x325x161	291x291	115 V a.c.	74/83	445/485	320/350	cURus; cULus; cCSAus
FF20A115UER	325x325x160	291x291	115 V a.c.	101/129	530/577	380/420	-
FF20A115UER1	325x325x161	291x291	115 V a.c.	74/83	530/575	380/420	cURus; cULus; cCSAus
FF20A230UE	325x325x161	291x291	230 V a.c.	92/116	460/510	325/360	-
FF20A230UE1	325x325x161	291x291	230 V a.c.	70/85	455/503	325/360	cURus; cULus; cCSAus
FF20A230UER	325x325x161	291x291	230 V a.c.	92/116	540/595	380/425	-
FF20A230UER1	325x325x161	291x291	230 V a.c.	70/85	540/590	380/420	cURus; cULus; cCSAus
FF20A400TUE	325x325x161	291x291	400 V a.c. 3 ~	99/124	537/632	361	-
FF20GA							
FF20GA115UE	325x325x159	291x291	115 V a.c.	143/177	708/775	505/550	-
FF20GA115UE1	325x325x159	291x291	115 V a.c.	110/156	675/738	495/520	cURus; cULus; cCSAus
FF20GA115UEA1	325x325x159	291x291	115 V a.c.	110/156	893/960	577/606	cURus; cULus; cCSAus
FF20GA115UER	325x325x159	291x291	115 V a.c.	124/192	760/845	580/620	-
FF20GA115UER1	325x325x159	291x291	115 V a.c.	102/145	760/850	570/630	cURus; cULus; cCSAus
FF20GA230UE	325x325x159	291x291	230 V a.c.	155/194	705/790	510/560	-
FF20GA230UE1	325x325x159	291x291	230 V a.c.	120/158	680/765	495/550	cURus; cULus; cCSAus
FF20GA230UEA	325x325x159	291x291	230 V a.c.	158/198	850/960	580/640	-
FF20GA230UEA1	325x325x159	291x291	230 V a.c.	120/158	895/998	573/650	cURus; cULus; cCSAus
FF20GA230UER	325x325x159	291x291	230 V a.c.	170/208	773/870	590/650	-
FF20GA230UER1	325x325x159	291x291	230 V a.c.	120/157	760/860	590/650	cURus; cULus; cCSAus
FF20GEA							
FF20GEA400TUE	325x325x149	291x291	400 V a.c. 3 ~	137/173	485	361	-
FF20GEA400TUER	325x325x150	291x291	400 V a.c. 3 ~	137/173	645/695	482/525	-
FF20PA							
FF20PA115UF	325x325x164	291x291	115 V a.c.	45/45	310/350	270/295	cURus; cULus
FF20PA115UFR	325x325x164	291x291	115 V a.c.	45/45	339/374	292/324	cURus; cULus
FF20PA230UF	325x325x164	291x291	230 V a.c.	45/45	315/345	270/290	cURus; cULus
FF20PA230UFR	325x325x164	291x291	230 V a.c.	45/45	334/367	294/317	cURus; cULus